

**Unique identifier of the product-type:**DRY-PRESSED CERAMIC TILES WITH WATER ABSORPTION  $E_b > 10\%$ ; Group BIII; GLAZED (GL)**Intended use or uses:**

CERAMIC TILES FOR INTERNAL WALLS IN BUILDINGS AND INDUSTRIAL FACILITIES

**Manufacturer:**

Ceramika Color Sp. z o.o.; Kopaniny 11b; 26-200 Końskie

**System or systems of assessment and verification of constancy of performance of the construction product:**

ASSESSMENT SYSTEM: 4

**Harmonised standard:**

EN 14411:2012

**Declared performance**

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction-to-fire performance	A1
Release of dangerous substances:	
- Lead	NPD
- Cadmium	NPD
- other	NPD
Bond strength / adhesion for:	
- cementitious adhesives	NPD
- dispersion adhesives	NPD
- reactive resin adhesives	NPD
- mortar	NPD
Durability, for:	
- internal uses:	Pass

The performance of the product referred to above is consistent with the set of declared performance/s.

This declaration of performance is issued in accordance with the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer specified above.

Signed for and on behalf of the manufacturer by:

**Magdalena Bąk**

  
**MAGDALENA BĄK**  
*Kierownik Działu Kontroli Jakości*

in Końskie, 10/01/2022